

⚠ CAUTION

- EN For outdoor use with cold water only. Do not spray near electrical connections. Maximum operating pressure 552kPa (5.5 bar).
- DA Kun til udendørs brug med koldt vand. Vand ikke i nærheden af elektriske installationer. Maksimalt driftstryk 552kPa (5,5 bar).
- DE Nur mit kaltem Wasser im Freien zu verwenden. Nicht in der Nähe von elektrischen Anschlüssen sprühen. Maximaler Betriebsdruck 552 kPa (5,5 bar).

Made in China
PN 97004-30 rB



www.orbitonline.com
Orbit® Irrigation Products, Inc.
North Salt Lake, UT 84054, USA
© 2013 Orbit® Irrigation Products, Inc.
All rights reserved. All trade names are registered trademarks of respective manufacturers listed.



CUSTOMER SERVICE
001-801-299-5555
www.orbitonline.com
info@orbiteuropa.com

4mm



4mm



Orbit

EN Mechanical Hose Tap Timer


- Timed watering up to 120 minutes
- Ergonomic swivel for easy hose attachment

DA Mekanisk vandhane timer

- Tidsstyret vanding op til 120 minutter
- Ergonomisk drejebelt for nem slangetilkobling

DE Mechanischer Timer mit Auslass

- Voreinstellung der Bewässerungsdauer auf bis zu 120 Minuten
- Ergonomischer Drehring für eine einfache Schlauchankopplung



97004

Orbit® 1.801.299.5555 orbitonline.com		<input checked="" type="checkbox"/> CMYK <input type="checkbox"/> Dieline <input type="checkbox"/> PMS 549 <input type="checkbox"/> PMS 0000 <input type="checkbox"/> PMS 0000 <input type="checkbox"/> PMS 0000		<input type="checkbox"/> Dims./Callout <input type="checkbox"/> Fold <input type="checkbox"/> Product Coverage <input type="checkbox"/> Glue		Printers are responsible for meeting print production requirements. Any changes must be approved by Orbit®. Printed piece must meet designer's specifications on this form. © 2015 Orbit Inc. This work is the property of Orbit®, and cannot be used, reproduced or distributed in any way without their express permission.
DATE: 12/03/2015		<input type="checkbox"/> Die <input type="checkbox"/> PMS 549 <input type="checkbox"/> PMS 0000 <input type="checkbox"/> PMS 0000		PRINTERS ARE REQUIRED TO MATCH ALL SPECIFIED PMS COLORS.		
DESIGNER: SH	MARKETING: AY	<input type="checkbox"/> Flat L: 000.000" W: 000.000" W: 000.000" H: 000.000" H: 000.000"		Additional Information . . .		
ARTWORK Nº: 97004-30 rB		<input checked="" type="checkbox"/> Folded L: 000.000" W: 000.000" W: 000.000" H: 000.000" H: 000.000"				
SOFTWARE: Adobe Indesign CS6						

EN Timed Watering:

Turn dial clockwise to desired minutes. To turn off, move dial to "0" and push up "Release Lever".

Manual (Non Timed) Watering:

To bypass timer, depress "Release Lever" and turn dial to "Manual On". To stop water turn dial to "0" and push up "Release Lever".

DA Tidsstyret vanding:

Drej drejeknappen med uret og til det ønskede antal minutter. For at slukke, drej drejeknappen til "0" og skub "Timerlåsen" op.

Manuel (ikke tidsstyret) vanding:

For at slukke tidsfunktionen, skub "Timerlåsen" og drej drejeknappen til "Manual On". For at stoppe vandet drej drejeknappen til "0" og skub "Timerlåsen" op.

DE Zeitgesteuerte Bewässerung:

Den Drehknopf im Uhrzeigersinn auf die gewünschte Anzahl an Minuten drehen. Zum Ausschalten den Knopf auf 0 zurück drehen und den Arretierhebel hochdrücken.

Manuelle Bewässerung:

Zum Umgehen des Timers den Arretierhebel herunterdrücken und den Drehknopf auf „Manual On“ (Manuell ein) drehen. Zum Abstellen des Wassers den Knopf auf 0 drehen und den Arretierhebel hochdrücken.

4mm



4mm



EN Time Indicator
DA Tidsindikator
DE Zeitanzeiger

EN Release Lever
DA Timerlås
DE Arretierhebel



Orbit